





STRONG HOLDER GUIDES FOR ACCESSORIES





CONFORTABLE DRIVING PLACE WITH SEAR AND CONTROLS EASILY ACCESSIBLE



ERGONOMIC STEERING WHEEL AND PARKING BRAKE LEVER



SMPLE ADVANCE FOOT PEDAL



TECHNICAL DATA

resistant to wear over time.

Rear hydrostatic transmission

- Rear hydrostatic transmission without maintenance, with foot pedal.
- Off road rear wheels, ribbed front wheels.
- ☑ Max full **speed** 10 km/h.
- ✓ 40 LPM 40 BAR 3-diaphragm **pump** with 3-way pressure regulator.
- ☑ 3 Hp 24V battery-operated **electric motor**.
- ✓ **24V battery**. Autonomy of work 4 hours (approximately), time of recharge 8 hours (approximately). Battery and charger included.
- ✓ Small size (width 75 cm).
- ✓ **Dimensions**200 L: 75x190x130 cm
- ✓ Empty weight200 L: 338 kg




HYDROSTATIC TRANSMISSION



EASY AND INTUITIVE CONTROL PANEL



INTEGRATED COMPARTMENT WITH ELECTRIC MOTOR AND PUMP



TURNING RADIUS OF 250 CM



14% MAXIMUM SLOPE





M.M. S.r.l.
Via R. Dalla Costa, 110
41122 Modena - ITALY
Tel. +39 059 25 16 54
Fax +39 059 25 17 11
mm@mmspray.it





