



## DEMOUNT SPRAYER FOR HIGH PRESSURE WASHING "GS-L" LINE

## **GS-L LINE**

- **✓ COMPACT**
- **✓ VERSATILE**
- CONFIGURABLE ACCORDING TO YOUR NEEDS
- ✓ TANK CAPACITY 500 L











**DEMOUNT SPRAYER GS-L** 

## **TECHNICAL DATA**

- ✓ Self-supporting steel tubular frame with epoxy powder coating, resistant to wear over time. Prepared for mounting on pick-up trucks, equipped with handles to be moved by hand, with forklifts or cranes.
- ✓ 10 m hose and lance supplied as standard for high pressure washing.
- ☑ 500 L **polyethylene tank** with filter.
- ☑ Piston pump:
  - XT: 11 L/min 140 bar
  - SXH: 15 L/min 120 bar.
- ☑ HONDA GX160 5.5 HP Engine
- ☑ Possibility to mount (optional):
  - manual hose reel with 20 m of hose
  - automatic spring loaded hose reel with 20 m of hose
- **☑** Dimensions

500 L: 90x130x127 cm

**☑** Weight

500 L: 90 kg

☑ Different tank sizes

1000 L: 102x210x160 cm 1500 L: 130x245x165 cm 2000 L: 145x255x165 cm



LANCE FOR HIGH PRESSURE WASHING (AS STANDARD)



HONDA GX160 ENGINE AND PISTON PUMP



AUTOMATIC SPRING LOADED HOSE REEL



M.M. S.r.l. Via R. Dalla Costa, 110 41122 Modena - ITALY Tel. +39 059 25 16 54 Fax +39 059 25 17 11



